


# 5/8 M16\* 3040 SERIES POWER OUTPUT VRS SENSORS



FOR SPEED SENSING APPLICATIONS WHERE LARGER ACTUATORS CAN BE USED.  
BEST FOR DRIVING LOW RESISTANCE LOADS AT LARGE AIR GAPS.

OPTIMUM ACTUATOR: 8 DP (Module 3.17) Ferrous Metal Gear


TEST CONDITION: B (See Pg. 8)

## GENERAL SPECIFICATIONS

OUTPUT VOLTAGE: 70V P-P min.  
COIL RESISTANCE: 120 to 162 OHMS  
POLE PIECE DIA.: .187" (4.75mm)  
MIN. SURFACE SPEED: 15 IPS (.38 m/Sec) Typical

OPER. TEMP. RANGE: -67 to 250F (-55 to 120C)  
INDUCTANCE: 85 mH max.  
GEAR PITCH RANGE: 12 DP (Module 2.11) or Coarser  
MAX. OPER. FREQ.: 40 KHz Typical


VIBRATION: Meets Mil-Std 202F Method 204D



### SENSORS WITH 5/8-18 UNF-2A MOUNTING THREAD\*, MS3106 CONNECTOR


MODEL	THREAD LENGTH	WEIGHT
3040AN	1.1" (28 mm)	2.5 oz. (70 gr.)
3040AN25	2.5" (63 mm)	3.0 oz. (84 gr.)
3040AN30	3.0" (76 mm)	3.0 oz. (84 gr.)
3040AN40	4.0" (101 mm)	3.5 oz. (98 gr.)
3040AN50	5.0" (127 mm)	4.5 oz. (128 gr.)

Mates with 41010(VR) Connector or CA210 Cable Assembly




### SENSORS WITH 5/8-18 UNF-2A MOUNTING THREAD\*, 24" (300 mm) LEADS

MODEL	THREAD LENGTH	WEIGHT
3040S20	2.0" (50 mm)	2.5 oz. (70 gr.)
3040S30	3.0" (76 mm)	3.0 oz. (84 gr.)



### SENSORS WITH 5/8-18 UNF-2A MOUNTING THREAD\*, 1 1/4-14 NPT CONDUIT MOUNT, 24" (300 mm) LEADS

MODEL	THREAD LENGTH	WEIGHT
3040H20	2.0" (50 mm)	5.0 oz. (140 gr.)



### SENSORS WITH 5/8-18 UNF-2A MOUNTING THREAD\*, MS3106 CONNECTOR, .312" THREAD RELIEF

MODEL	THREAD LENGTH	WEIGHT
3040A	1.4" (35 mm)	2.5 oz. (70 gr.)
3040A25	2.5" (63 mm)	3.0 oz. (84 gr.)

Mates with 41010(VR) Connector or CA210 Cable Assembly

\*For M16 x 1.5 G Mounting Thread Versions, add "M" as the first character of the model number.  
Contact your local distributor for availability and pricing.



ISO  
9001

