

PR600 Non-Contact Phase Rotation Tester

Clip on to insulated wires with a maximum conductor diameter of 1.3" (33mm)

Features:

- Determines correct phase wiring sequence for 3-phase system installation
- View results on an easy-to-read LED display to see phase direction (clockwise/counterclockwise) and which phases are live
- Buzzer sounds to indicate live wire and clockwise (intermittent beep) or counter clockwise (continuous beep) direction
- 2 selectable brightness levels for use in sunlight or dimly lit areas
- Back cover magnet mounts on metal surfaces for hands-free operation
- Auto power off
- Low Battery indicator
- CAT IV 600V safety category
- Includes 59" (1.5m) test leads with large color-coded alligator clips, 9V battery and soft case

Applications:

Determine correct wiring sequence for 3-phase systems



Specifications

| | |
|------------------------|----------------------------------|
| Voltage Range | 75 to 1000VAC |
| Bandwidth | 45 to 65Hz |
| Max Conductor Diameter | 1.3" (33mm) |
| Power | 9V Battery |
| Safety Category | CAT IV 600V |
| Dimensions | 5 x 2.8 x 1.8" (128 x 72 x 46mm) |
| Weight | 13.2oz (375g) |

Ordering Information:

PR600 Non-Contact Phase Rotation Tester

