



DC Ammeter Shunts

Accuracy: 1/4%

Recommended continuous operation: <2/3 rated current

TYPE CA: 1 through 500 Amperes



TYPE CA: 50 mV

Catalog Number	AMP	A	B
CA1A50*	1	1.45	0.50
CA2A50*	2	1.45	0.50
CA5A50*	5	1.45	0.50
CA10A50*	10	1.45	0.50
CA20A50	20	1.45	0.50
CA50A50	50	1.45	0.50
CA100A50	100	1.45	0.50
CA150A50	150	1.45	0.50
CA200A50	200	1.45	0.50
CA250A50	250	1.75	0.75
CA300A50	300	1.75	0.75
CA400A50	400	1.75	0.75
CA500A50	500	1.75	0.75

TYPE CA: 100 mV

Catalog Number	AMP	A	B
CA1A100*	1	1.45	0.50
CA2A100*	2	1.45	0.50
CA5A100*	5	1.45	0.50
CA10A100*	10	1.45	0.50
CA15A100	15	1.45	0.50
CA20A100	20	1.45	0.50
CA25A100	25	1.45	0.50
CA50A100	50	1.45	0.50
CA75A100	75	1.45	0.50
CA100A100	100	1.45	0.50
CA200A100	200	1.45	0.50
CA300A100	300	1.75	0.75
CA500A100	500	1.75	0.75

*Low amperage models are furnished with protective covers.

