



*The Model 60 features a High-Impact Case that's guaranteed to withstand a 5 foot drop!*



## Model 60

*The drop resistant, overload protected VOM for demanding field use.*

- ▲ With our unique 3 fuse protection (including 2A/1000V fuse) the Model 60 is, quite possibly, the best protected VOM in the industry
- ▲ Mirrored scale to reduce parallax error
- ▲ Confidence Test to check batteries, fuses, leads and meter accuracy
- ▲ Decibel function for audio work
- ▲ 28 Ranges and Functions
- ▲ High Impact Orange Case
- ▲ AC/DC Voltage to 1000V
- ▲ DC Current to 1000mA
- ▲ Resistance to 10M $\Omega$
- ▲ Decibel ranges from -20dBm to +52dBm
- ▲ Polarity Reversing Switch
- ▲ AC Voltage frequency response to 40KHz typical
- ▲ 3 Year Warranty

**Cat. No. 3145: Model 60**

## Model 630

*The industry standard for laboratory, bench and field testing.*

- ▲ Single range switch to help reduce chance of operator error
- ▲ Diode overload protection and 2 fuse arrangement
- ▲ Mirrored scale to reduce parallax error
- ▲ Decibel function for audio work
- ▲ All ranges are fuse protected
- ▲ Thermoset plastic case
- ▲ 25 Ranges and Functions
- ▲ Glass meter window for added chemical resistance
- ▲ Two input jacks to help minimize error
- ▲ AC Voltage frequency response to 40KHz typical
- ▲ Resistance measurement of 30V / 100M on Rx100K range for testing insulation
- ▲ 3 Year Warranty

**Cat. No. 3030: Model 630**



# TRIPLETT Analog Tester Selection Guide

<b>Model Number</b> <i>Catalog Number</i>		<b>310</b> <i>Cat. No. 3018</i>	<b>310-C</b> <i>Cat. No. 3022</i>	<b>60</b> <i>Cat. No. 3145</i>	<b>630</b> <i>Cat. No. 3030</i>
<b>FUNCTIONS</b>	<b>DC Voltage</b>	5 (3000mV to 1200V) 3% full scale 20K $\Omega$ / Volt	5 (3000mV to 600V) 3% full scale 20K $\Omega$ / Volt	8 (300mV to 1000V) 1.5% full scale 20K $\Omega$ / Volt	6 (300mV to 600V) 1.5% full scale 20K $\Omega$ / Volt
	<b>AC Voltage</b>	5 (3V to 1200V) 4% full scale 5K $\Omega$ / Volt	5 (3V to 600V) 4% full scale 15K $\Omega$ / Volt	6 (3V to 1000V) 3% full scale 5K $\Omega$ / Volt	5 (3V to 600V) 3% full scale 5K $\Omega$ / Volt
	<b>DC Current</b>	4 (0.6mA to 0.6A) 3% full scale 250mV / 330mV	4 (0.6mA to 0.6A) 3% full scale 250 / 330mV	4 (0.1mA to 1A) 1.5% full scale 320mV	4 (0.6mA to 0.12A) 1.5% full scale 300mV
	<b>Resistance</b>	4 (20K $\Omega$ to 20M $\Omega$ ) 3% full scale	4 (20K $\Omega$ to 20M $\Omega$ ) 3% full scale	5 (1K $\Omega$ to 10M $\Omega$ ) 1.5% full scale	5 (1K $\Omega$ to 100M $\Omega$ ) 1.5% full scale
	<b>dB Ranges</b>	—	—	5 (-20dBm to +52dBm)	5 (-20dBm to +57dBm)
	<b>Total Ranges / Functions</b>	18	18	28	25

<b>SAFETY</b>	<b>Meter Protection</b>	Diode Meter Protection	Diode Meter Protection	Diode Meter Protection Gas Discharge Tube	Diode Meter Protection
	<b>Fuse</b>	1/16A / 250V	1/16A / 250V	1/8A / 250V 1A / 250V 2A / 1000V	2A / 600V 1A / 250V

<b>FEATURES</b>	<b>Polarity Reversing Switch</b>	—	▲	▲	—
	<b>High Accuracy</b>	—	—	▲	▲
	<b>Mirrored Scale</b>	—	—	▲	▲
	<b>X-tra Rugged Case</b>	—	—	▲	—
	<b>Hand-Sized</b>	▲	▲	—	—
	<b>Confidence Test</b>	—	—	▲	—

<b>PHYSICAL</b>	<b>Battery</b>	1 - 12V, 1 - N-Cell	1 - 12V, 1 - N-Cell	1 - 9V, 1 - D-Cell	1 - 30V, 1 - D-Cell
	<b>Dimensions</b>	2.75 x 1.3 x 4.25 in.	2.75 x 1.3 x 4.25 in.	3.25 x 5.25 x 7.25 in.	3.3 x 5.5 x 7.5 in.
	<b>Weight</b>	2 lbs.	2 lbs.	4 lbs.	5 lbs.

