

3388 – Fox & Hound HotWire™

Live wire Tone & Probe Kit traces powered 120/220VAC circuits (250VAC max)

Features:

- Trace other powered or unpowered common wires including telephone and cable TV wires, LAN cables, security system wires, invisible fences, and landscape lighting
- Locate wires through drywall, plaster, wood, cement, etc., and buried wires up to 6"
- Trace wires up to 1000 feet in length
- Adjustable Sensitivity
- Audible and Visual Notification
- High output, warble/pulse selectable tracer tone
- Includes Test Leads (24" and 60"), flat blades, pointed probes, alligator clips, (2) 9V batteries, and hard carrying case



Hotwire Fox	
Operating Frequency (RF)	400kHz to 500kHz
Operating Frequency (AF)	800Hz to 2400Hz
Output Voltage (RF)	adjustable 5vpp to 30vpp (open circuit)
Output Voltage (AF)	fixed 10vpp (open circuit)
Tracer Tone	Warble or Pulsed, High or Low Pitch
Max. AC/DC Live Voltage	250V
Continuity Test	Up to 5,000 ohms with audible beeper
AC Voltage Test	30VAC to 250VAC
DC Voltage Test	Positive applied to red test lead 40VDC to 250VDC
Dimensions/Weight	3.5 x 4.5 x 1.5" (89 x 114 x 38mm) / 7 oz (198g)
Hotwire Hound	
Operating Frequency (RF)	400kHz to 500kHz
Signal Indicators	Speaker outputs Tracer signal and LED indicates signal strength
Earphone Jack	Accepts 1/8" mono or stereo earphone plug (mutes speaker)
Headlights	2 High Brightness White LEDs
Speaker	1.5" Mylar cone with Alnico magnet
Dimensions	1-7/8" (48mm) dia at speaker; 1-3/8" (35mm) dia at body; 7.5" (191mm) long
Weight	9 oz (255g)

Ordering Information:

3388 Fox & Hound HotWire Live Wire Tone & Probe Kit