

B SERIES

DC INSTRUMENT SHUNTS THROUGH 800 AMP

B SERIES 50 MILLIVOLT

CATALOG NO.	AMP	A	C	D	G	H	J
B200A50	200	4	6	2	2	.5	.391
B250A50	250	4	6	2	2	.625	.391
B300A50	300	4	6	2	2	.625	.391
B400A50	400	4	6	2	2	.875	.391
B500A50	500	4	6	2	2	1	.391
B600A50	600	4	6	2	2	1	.531
B750A50	750	4	6	2	2	1.25	.531
B800A50	800	4	6	2	2	1.25	.531

DIMENSIONS IN INCHES
DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

B SERIES 100 MILLIVOLT

CATALOG NO.	AMP	A	C	D	G	H	J
B200A100	200	6	8	2	2	.5	.391
B250A100	250	6	8	2	2	.625	.391
B300A100	300	6	8	2	2	.625	.391
B400A100	400	6	8	2	2	.875	.391
B500A100	500	6	8	2	2	1	.391
B600A100	600	6	8	2	2	1	.531
B750A100	750	6	8	2	2	1.25	.531
B800A100	800	6	8	2	2	1.25	.531

ADJUSTED ACCURACY $\pm .25\%$
RATED ACCURACY $\pm .33\%$

