MICRO-OHMMETERS

MODEL 6240

Auto calculates resistance from $5\mu\Omega$ to 400Ω with resolutions down to $1\mu\Omega$



3. <u>23. 13. 13. 13. 13. 13. 13. 13. 13. 13. 1</u>							
MODEL	6240						
Range	4000μΩ	40mΩ	400mΩ	4000mΩ	40Ω	400Ω	
Accuracy	±0,25% of Reading ±2cts						
Resolution	1μΩ	10μΩ	0.1mΩ	1mΩ	10mΩ	100mΩ	
Test Current	10A	1A	1A	100mA	10mA	10mA	
Max. Inductive Load	0 to 5 H						
Memory	Stores up to 99 test results						
Power Source	Rechargeable 6V, 8.5Ah NiMH battery pack (included)						



Extra large tool bag, set of two 10ft Kelvin clips (10A-Hippo), set of two 10ft Kelvin probes (1A - Spring Loaded), optical USB cable, US 115V power cord, two spare fuses (12.5A), NiMH rechargeable battery pack, and USB drive suppled with product user manual and DataView® software.











FEATURES

- Reliable low resistance measurements from $5\mu\Omega$ to 400Ω
- Four-terminal Kelvin resistance measurement eliminates test lead resistance
- 10A test current up to 4000μΩ
- ±0.25% basic accuracy
- 1μΩ resolution
- Direct reading, easy to operate
- Six selectable resistance ranges
- Reverse polarity switch
- Overload and input fuse protection
- Manufactured to international safety and environmental standards
- Automatic decimal point and zeroing
- Large terminals accept banana plugs and spaded lugs
- Rechargeable NiMH battery with internal charger (110/220V)
- Large multifunctional backlit display
- Includes power cord and isolated USB cable
- Includes FREE DataView® software for data retrieval, real-time display, analysis and report generation

ACCESSORIES

KELVIN CLIPS, SET OF TWO

Catalog #1017.84 (replacement) (10A - Hippo) 10ft Catalog #2118.70 (optional) (10A - Hippo) 20ft



KELVIN CLIPS, SET OF TWO

Catalog #2118.79 (optional) (1-10A) 10ft

Catalog #2118.80 (optional) (1-10A) 20ft



KELVIN PROBES, SET OF TWO

Catalog #2118.77 (optional) (10A - spring loaded) 10ft Catalog #2118.78 (optional) (10A - spring loaded) 20ft



CATALOG NO. DESCRIPTION

2129.80	Micro-Ohmmeter Model 6240 (10A)	
Accessories/Rep	placement - available on website store from www.aemc.com	
1017.84	Kelvin Clips 10ft (10A – Hippo)	
2118.70	Kelvin Clips 20ft (10A - Hippo)	
2118.73	Kelvin Probes 10ft (1A, Spring Loaded)	
2118.74	Kelvin Probes 20ft (1A, Spring Loaded)	
2118.75	Kelvin Probes Pistol Grip (10A – Spring Loaded), 10ft	
2118.76	Kelvin Probes Pistol Grip (10A – Spring Loaded), 20ft	
2118.77	Kelvin Probes (10A – Spring Loaded), 10ft	
2118.78	Kelvin Probes (10A - Spring Loaded), 20ft	
2118.79	Kelvin Clips 10ft (1-10A) Replacement for Cat #2118.71	
2118.80	Kelvin Clips 20ft (1-10A) Replacement for Cat #2118,72	