



Model number	FoodPro	FoodProPlus
<b>Application</b>		
Recommended Uses	Food inspection, food service, HACCP programs	Food inspection, food service, HACCP programs
<b>Infrared/ Noncontact</b>		
Noncontact Temperature Range	-30 °C to 200 °C (-25 °F to 390 °F)	-30 °C to 275 °C (-25 °F to 525 °F)
Accuracy	+1 °C (2 °F) 0 °C to 65 °C (32 °F to 150°C)	+1 °C (2 °F) 0 °C to 65 °C (32 °F to 150°C)
Distance to Spot (D:S)	2.5:1	2.5:1
Sighting	LED illumination	LED illumination
Typical Distance to Target	Up to 250 mm (10 in)	Up to 250 mm (10 in)
<b>Contact</b>		
Temperature Range		-40 °C to 200 °C (-40 °F to 390 °F)
<b>Data Storage and Download</b>		
<b>Special features</b>		
Material type adjustment (emissivity)	Preset for food	Preset for food
High and Low alarms	Low and high out of safe range LEDs	Low and high out of safe range LEDs
Sealing for liquid	IP54 (hand washable, not submersible)	IP54 (hand washable, not submersible)
<b>Physical</b>		
Form Factor	Pistol	Pistol
Dimensions, approximate (H x W x D)	14.5 cm x 3 cm x 5 cm (5.25 in x 1.25 in x 2 in)	16.5 cm x 3 cm x 5.3 cm (6.5 in x 1.25 in x 2 in)
Battery	AA	9V
Case	Soft case	Soft case
Warranty	2 years	2 years

Fluke Corporation  
PO Box 9090, Everett, WA USA 98206

Fluke Europe B.V.  
PO Box 1186, 5602 BD  
Eindhoven, The Netherlands

For more information call:  
In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0) 40 2675 200 or  
Fax +31 (0) 40 2675 222  
In Canada (800) 36-FLUKE or  
Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2007 Fluke Corporation. All rights reserved.  
Specifications subject to change without notice.